

Ambu® aView™

Portable monitor for aScope 2, aScope 3 and aScope 3 Slim



Key Benefits

- Portable touch-screen monitor
- Operational in seconds
- Intuitive user interface
- Easy file transfer by USB
- Minimum 3 hours battery time

Ambu® aView™

Intubation and bronchoscopy made easy – in the OR, ER and ICU
Ambu® aView™ is a portable high resolution monitor that is compatible with all of Ambu's single-use flexible videoscopes: aScope 3, aScope 3 Slim and aScope 2.

aView is portable and easy to set up - on a table as well as on an IV pole. When turned on the image appears in just a few seconds.

A higher level of practicality

The portable plug and play system is easy to transport and set up. When connected to an aScope 3 the user-friendly touch-screen

and the high resolution image enables easy navigation and fast identification of anatomical landmarks. Together with an aScope 3 it facilitates a wide range of ICU, OR and ER procedures, on an as-needed basis.

The user-friendly intuitive operation mode allows images or videos to be stored for later reference. The USB interface enables an easy transfer of files.

Specifications

Display	
Max. resolution	800 * 480
Orientation	Landscape
Display type	8.5" colour TFT LCD
Brightness control	Yes, ("+" / "-")
Contrast control	Yes, ("+" / "-")
Start up time	About 1 second
Electrical power	
Power requirement	18V 1,67A DC input
Battery type	11,1V 3760mAh
Operating environment, storage & transportation	
Temperature	10 ~ 40° C (50 ~ 104° F)
Relative humidity	30 ~ 85%
IP Protection Classification System	The aView is classified IP30.
Atmospheric pressure	80-109 kPa
Altitude	≤ 2000m
Dimensions	
Width	241mm (9.49")
Height	175mm (6.89")
Thickness	33,5mm (1,32")
Weight	1500g (331lbs)
Connections	
USB connection	Type A
Mounting interface	
Mounting interface standard	VESA MIS-D, 75 C, VESA FDMI compliant display, Part D, with centre located mounting interface



Ambu® aView™ and
Ambu® aScope™ 3



Ambu® aView™ on IV Pole

aView power supply	
Weight	360g (0.79 lbs)
Electrical power	
Power requirement	100 - 240V AC; 50-60Hz; 0.6A
Power out	18V DC; 1.67A
Storage	
Temperature	10 ~ 40°C (50 ~ 104°F)
Relative humidity	10 ~ 90%

Ordering specifications

Item no.	Quantity (Ambu® aView™)
405001000	1