smiths medical graseby



Graseby[™] 1200 Infusion pump

Affordable quality from a name you can trust



GRASEBY[™] 1200 INFUSION PUMP

Widely used in Intensive Care Units (ICUs), Operating Rooms (OR) and general wards around the world, Graseby™ infusion pumps have long beer acknowledged and trusted by clinical professionals for over 30 years.

GRASEBY™ 1200 INFUSION PUMP PROVIDES CLINICIANS WITH QUALITY AND RELIABILITY AT A REASONABLE COST





environmental conditions

RS232 Communication Interface

STANDARD RS232 INTERFACE

The pump has a standard RS232 interface for bi- directional communication.

Interface

Graseby[™] 1200 Infusion Pump

EASY TO USE

• Light weight

- Option to use 9 different brands of infusions sets which includes 5 frequently used brands that have been pre-calibrated
- Direct rate input or automatic calculation of delivery rate based on volume and time setting
- Infusion set loading guidelines displayed on the top of the pump
- Removable pump mechanism that is easy to clean

SAFETY


- Post occlusion bolus reduction
- Ultrasonic air sensor detects and alerts the patient and clinician if air is present in infusion set
- Built-in features to prevent free flow of drugs

RELIABILITY

- Infusion accuracy of ±5%
- Built-in rechargeable Lithium lon battery

PRE-CALIBRATED FOR 5 **BRANDS OF INFUSION SETS**

Set-up Two Infusion Programs at a Time



B.Br. Time	01 hr 30 手			
Volume 900.0mL				
1 Rate	600mL/h 出			
Total	0.0mL M			

- Clinicians can set-up two infusion programs at a time. Once the first phase is completed, the pump will switch to the second phase automatically.
- Easy-to-use workflow •
- Saves clinician's time





TECHNICAL FEATURES AND PARAMETERS

	Graseby [™] 1200 Infusion Pump	
Infusion Rate	1 mL/h to 1200 mL/h	
Flow Accuracy	±5% (accuracy of qualified infusion set after calibration)	
Priming / Bolus Dosage Rate	1000 mL/h	
Infusion Volume	1 mLto 9999 mL	
Accumulative Volume	0 mL to 9999 mL (0.1 mL increment)	
History Records	Up to 1500 records	
Occlusion Alarm Threshold	High: 107.1 kPa to 174.8 kPa Middle: 54.1 kPa to 110.2 kPa Low: 2 kPa to 45.1 kPa	
Ultrasonic Bubble Detector Sensitivity	≥25 µL	
KVO Rate	0 mL/h to 5 mL/h (adjustable, 1mL/h increment)	
Power Supply	AC 110-230 V~ 50-60 Hz; Built-in battery: DC12V rechargeable lithium iron phosphate battery can allow the pump to operate at the infusion rate of 25 mL/h (middle infusion rate specified in EN60601-2-24: 2015) for over 5.5h, after it is charged for 16 hours.	
Dimensions	282 mm (L) × 170 mm (W) × 120 mm (H)	
Weight	2 kg (include I.V clamp, customizable)	
Infusion Set	Compatible with 9 different brand of disposable infusion sets (5 brands pre-calibrated by the factory, see Table 1).	
	It is recommended that the users calibrate any brand not listed before using for the first time.	
	Table 1	

Table 1	
Serial Number	Brand / Manufacturer
-01-	B.Braun (B.Br.)
-02-	Lifeline (Lif.)
-03-	Romsons (Rom.)
-04-	Polymed (Pol.)
-05-	JMS

ORDERING INFORMATION

Graseby™ 1200 Infusion Pump				
Product	Language	Voltage	Power Cord	
08D3X100	English	110 - 230	IN Std (Plug based on BS 546)	
08D3W100	English	110 - 230	EU Std (CEE7/7 Schuko)	
08D3H100	English	110 - 230	IL Std (SI-32)	
08D3V100	English	110 - 230	IT Std (CEI 23-16/VII Plug)	
08D3Y100	English	110 - 230	GB Std (BS 1363)	
08D3S100	English	110 - 230	US Std (NEMA5-15 Hospital grade)	
08D2S100	English	110 - 230	US Std (NEMA5-15 Hospital grade)	

For more information visit www.smiths-medical.com

NOT AVAILABLE FOR SALE IN THE U.S.A.

PRODUCT(S) DESCRIBED MAY NOT BE LICENSED OR AVAILABLE FOR SALE IN CANADA AND OTHER COUNTRIES

Smiths Medical International

1500 Eureka Park, Lower Pemberton Ashford Kent, TN25 4BF Tel: +44 (0)845 850 0445 www.smiths-medical.com

Find your local contact information at: www.smiths-medical.com/customer-support/contact-us

Smiths Medical is part of the global technology business Smiths Group plc. Please see the Instructions for Use/Operator's Manual for a complete listing of the indications, contraindications, warnings and precautions. Graseby and the Smiths Medical design mark are trademarks of Smiths Medical. The symbol ® indicates the trademark is registered in the U.S. Patent and Trademark Office and certain other countries. All other names and marks mentioned are the trademarks or service marks of their respective owners. ©2016 Smiths Medical. All rights reserved. IN193908GB-112016

MZHCCA-0008



smiths medical